

Technical drawing of a 4-way hydraulic valve, showing three views: top, side, and front.

Top View:

- Port specification: $\square 27^{+0.033}_0$ DP27
- Port types: 4-M10-DP15-Ø102 and 4-M12-DP18-Ø125

Side View:

- Port height: 30
- Body width: 408.5 ± 1.5

Front View:

- Port spacing: 130 and 80
- Port height: 30
- Port types: M5DP8 and G 1/4"

Model	2.5bar	3.0bar	3.5bar	4.0bar	4.5bar	5.0bar	5.5bar	6.0bar	7.0bar	8.0bar
DR00450-K	217	261	304	348	391	434	478	521	608	695

Model	Number of springs	Air pressure torque																				Spring return torque	
		2.5bar		3.0bar		3.5bar		4.0bar		4.5bar		5.0bar		5.5bar		6.0bar		7.0bar		8.0bar		90°	0°
		0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°		
		Start	End	Start	End	Start	End	Start	End	Start	End	Start	End	Start	End	Start	End	Start	End	Start	End		
SC00450-K	05	135	88.2	178	132	222	175	265	219	309	262	352	305									129	82.3
	06	119	62.4	162	106	205	149	249	193	292	236	336	280	379	323							155	98.7
	07			146	80.1	189	124	232	167	276	210	319	254	363	297	406	341					181	115
	08					173	97.7	216	141	259	185	303	228	346	272	390	315	477	402			206	132
	09							200	115	243	159	286	202	330	246	373	289	460	376	547	463	232	148
	10									227	133	270	177	313	220	357	263	444	350	531	437	258	165
	11											254	151	297	194	340	238	427	324	514	411	284	181
	12													280	168	324	212	411	299	498	386	310	197

DR 15.5
SC 18.7

Date _____